

PUBLIC PRODUCT DATASHEET

High voltage Reed Relay

HVR12-1A20 is part of the High Voltage Reed Relay range from SHR MiRelay. This English public datasheet has been rebuilt under the current SHR AUTOSENSOR TECH LIMITED identity for customer selection, sample purchase and RFQ support.

Product Family High Voltage Reed Relay	Model HVR12-1A20	Purchase Path Sample order or RFQ confirmation
Manufacturer SHR AUTOSENSOR TECH LIMITED	Website www.reed-relay.com	Sales Contact sales@reed-relay.com
Contact Form 1A: 1 Form A; 1B: 1 Form B	Contact Rating 50	Max. Carry Current t 60 deg C A 5.0
Contact Resistance , excellent lifetime characteristics	Insulation Resistance , up to 1012Ω	Operate Time 3.0

Key Features

- High power reed relay with dielectric strength up to 20KV DC
- High carry current
- High Insulation resistance, up to 1012Ω
- Low contact resistance, excellent lifetime characteristics
- Custom Design, conforming to Rohs directive

Technical Specifications

Parameter	Value
Contact Form	1A: 1 Form A; 1B: 1 Form B
Contact Rating	50
Max. Carry Current	t 60 deg C A 5.0
Contact Resistance	, excellent lifetime characteristics
Insulation Resistance	, up to 1012Ω
Operate Time	3.0
Release Time	1.5
Operating Temperature	deg C -20+70
Storage Temperature	deg C -35+105

Specification Notes

HVR Series(10KV&15KV&20KV)

High voltage Reed Relay

1 Feature

High power reed relay with dielectric strength up to 20KV DC

High carry current

High Insulation resistance, up to 1012Ω

Low contact resistance, excellent lifetime characteristics

Custom Design, conforming to Rohs directive

2 Performance Data

Relay Model / HVR-10- HVR-15- HVR-20-

Contact Rating W 50

Max.Switching Voltage (Max DC/Peak AC) V 7500 10000

Max.Switching Current (Max DC/Peak AC) A 3.0

Max.Carry Current at 60 deg C A 5.0

Contact Resistance mΩ 150 200

Dielectric

Strength

(static)

Between contact V 10000 15000 20000

Contact/shield to coil V 15000 20000

Contacts to shield V 15000 20000

Insulation Resistance Ω 1012

Operate Time ms 3.0

Release Time ms 1.5

Vibration(0-2000Hz) G 20

Shock(11ms, 1/2 sine) G 50

Operating Temp deg C -20-+70

Storage Temp deg C -35-+105

Life Expectancy Ops 5×10^7 (at 500VDC-100mA)

Outline Dimensions / Reference outline drawing

3 Coil Parameters

Model Nominal Voltage

(VDC)

Pickup Voltage

Max.(VDC)

Dropout Voltage

Min.(VDC)

Operate Voltage

Coil Resistance

($\pm 10\% \Omega$ at 20 deg C)

HVR-

4 0.5 7 30

12 9 1 16 200

24 18 2 29 600

SHR SENSOR & RELAY

sales@reed-relay.com

4 Example of order marking

HVR - - -(XXX)

① ② ③ ④ ⑤ ⑥

① Product model: HVR

② Nominal coil voltage: 05: 5VDC; 12: 12VDC; 24: 24VDC

③ Contact form: 1A: 1 Form A; 1B: 1 Form B

④ Breakdown voltage: 10: 10KV; 15: 15KV; 20: 20KV

⑤ Pin type: 02; 04; 06; 150; 156

⑥ Special code: Customer special requirement

5 Outline drawing

1) HVR-1A-02

2) HVR-1A-04

3) HVR-1B-04

4) HVR-1A-06

Ordering & Engineering Support

For production projects, confirm coil voltage, contact form, switching voltage/current, load type, operating environment, target quantity and required approvals before release. Contact sales@reed-relay.com or +86 137 6157 1029 for datasheet confirmation, sample availability and cross-reference support.

Address: Room 311, No. 18 Hangchuan Road, Pudong New District, Shanghai, China

Document rebuilt: 2026-05-05 | Source filename: HVR12-1A20.pdf