


DIL-2A05B


- Hermetically sealed for long life
- Low Contact Resistance
- Excellent Lifetime Characteristics
- Custom Design Available



[Outline Dimension]


Unit: mm

Scale: 1/1



[Pin Layout]

[Top View]



Order Information

DIL-2A05B

Coil Parameters		Relay Parameters	
1 Nominal coil voltage	5 VDC	1 Min Breakdown Voltage	250 VDC
2 Max Operating voltage	7.5 VDC	2 Dielectric Strength coil/contact	1400 VDC
3 Max Pull-in voltage	3.5 VDC	3 Insulation Resistance coil/contact	1.00E+10ohm
4 Min Drop-out voltage	0.75 VDC	4 Operate Time, incl. Bounce	0.3ms
5 Coil Resistance	200 ohm	5 Reset Time	0.3ms
Contact Parameters		6 Capacitance Across Contacts	1.0pF
1 Contact Form	2 Form A	7 Storage Temperature	-35~+105°C
2 Max Contact Rating	10 W	8 Operating Temperature	-20~+70°C
3 Max Switch Voltage	200V ACpeak/DC	9 Soldering Temperature	5 sec. max 260°C
4 Max Switch Current	0.5 A		
5 Max Carrying Current	1.0 A		
6 Min Breakdown Voltage	250 VDC		
7 Max Contact Resistance	150 mohm		

Version: 01

Designed by

Checked by

Approved by

Date


20th, Sept, 2023

TITLE

High Voltage Reed Relay

P/N

DIL-2A05B



Scale: 1:1

Page: 1/1