


## HVR12-2A06-P00

### High Voltage Reed Relay

#### PRODUCT VISUAL



#### KEY RATINGS

COIL VOLTAGE  
**12 VDC**

CONTACT FORM  
**2 Form A**

SWITCH VOLTAGE  
**1 kV**

CONTACT RATING  
**100 W**

#### OVERVIEW

- High voltage reed relay
- Breakdown up to 7 kVDC
- Custom design available
- Low contact resistance
- 2 Form A source schematic

#### COIL DATA

Nominal Coil Voltage	<b>12 VDC</b>
Nominal Current	<b>48 mA</b>
Coil Resistance	<b>250 Ω</b>
Max Pull-in Voltage	<b>9 VDC</b>
Min Drop-out Voltage	<b>1 VDC</b>

#### CONTACT RATINGS

Contact Form	<b>2 Form A</b>
Max Contact Rating	<b>100 W</b>
Max Switch Voltage	<b>1000 VACpk/VDC</b>
Max Switch Current	<b>1.0 A</b>
Max Carrying Current	<b>2.5 A</b>
Min Breakdown Voltage	<b>7 kVDC</b>
Max Contact Resistance	<b>150×2 mΩ</b>


#### ELECTRICAL CHARACTERISTICS

Dielectric Open / Contact-Coil	<b>7 / 7 kVDC</b>
Insulation Contact-Coil	<b>1×10<sup>12</sup> Ω</b>
Operate Time incl. Bounce	<b>1.0 ms</b>
Reset Time	<b>0.1 ms</b>
Capacitance Across Contacts	<b>0.2 pF</b>


#### ENVIRONMENTAL / OPTIONS

Operating Temperature	<b>-20°C to +70°C</b>
Storage Temperature	<b>-35°C to +105°C</b>
Soldering Temperature	<b>260°C, 5 sec max</b>

#### MECHANICAL OUTLINE / DIMENSIONS



#### CIRCUIT / MARKING / TERMINAL VIEW



#### ORDERING & SOURCE TRACEABILITY

**HVR12-2A06-P00 — 12 VDC coil, 2 Form A source schematic, 7 kVDC breakdown, P00 variant**

Source: HVR12-2A06-P00.pdf

Technical values are preserved from source PDFs / generated metadata. Original outline and circuit figures are reused where available; do not treat artwork proportions as standalone dimensional authority.