

## HVR12-2A15-150

### High Voltage Reed Relay

#### PRODUCT VISUAL



embedded pdf product render with exact hvr12 2a15 150 marking

#### KEY RATINGS

COIL VOLTAGE  
**12 VDC**

CONTACT FORM  
**2 Form A**

SWITCH VOLTAGE  
**10 kVDC**

CONTACT RATING  
**50 W**

#### OVERVIEW

- High voltage reed relay
- Breakdown up to 15 kVDC
- Excellent lifetime characteristics
- Low contact resistance
- 150 mm lead option

#### COIL DATA

Nominal Coil Voltage	<b>12 VDC</b>
Nominal Current	<b>80 mA</b>
Coil Resistance	<b>150 ± 10% Ω</b>
Max Pull-in Voltage	<b>9 VDC</b>
Min Drop-out Voltage	<b>1 VDC</b>

#### CONTACT RATINGS

Contact Form	<b>2 Form A</b>
Max Contact Rating	<b>50 W</b>
Max Switch Voltage	<b>10 kVDC</b>
Max Switch Current	<b>3.0 A</b>
Max Carrying Current	<b>5.0 A</b>
Min Breakdown Voltage	<b>15 kVDC</b>
Max Contact Resistance	<b>150 mΩ</b>
Life Expectancy	<b>5 × 10<sup>7</sup> ops @ 500V 100mA</b>


#### ELECTRICAL CHARACTERISTICS

Dielectric Open / Contact-Coil	<b>15 / 15 kVDC</b>
Insulation Open / Contact-Coil	<b>1 × 10<sup>12</sup> Ω each</b>
Operate Time incl. Bounce	<b>3.5 ms</b>
Reset Time	<b>2.0 ms</b>
Capacitance	<b>1.0 pF across open switch</b>



#### ENVIRONMENTAL / OPTIONS

Vibration	<b>20 G, 10-2KHz 1.5mm</b>
Shock	<b>50 G, 11ms half-sine</b>
Operating Temperature	<b>-20°C to +70°C</b>
Storage Temperature	<b>-35°C to +105°C</b>
Soldering Temperature	<b>260°C, 5 sec max</b>
Washability	<b>Fully sealed</b>

#### MECHANICAL OUTLINE / DIMENSIONS



#### CIRCUIT / MARKING / TERMINAL VIEW



#### ORDERING & SOURCE TRACEABILITY

**HVR12-2A15-150 — HVR, 12 = 12 VDC, 2A = 2 Form A, 15 = 15 kVDC, Pin Out = 150, Special = Nil**

Source: HVR12-2A15-150.pdf

Technical values are preserved from source PDFs / generated metadata. Original outline and circuit figures are reused where available; do not treat artwork proportions as standalone dimensional authority.