





400-133

- High Voltage Reed Relay
- Low Contact Resistance
- Breakdown up to 5 kVDC
- Excellent Lifetime Characteristics
- Custom Design Available



Outline Dimension

Unit: mm DIM Tolerance: ±0.3



Coil Parameters (at 20℃)

Nominal Coil Voltage	Nominal Current	Coil Resistance	Max Pull-in Voltage	Min Drop-out Voltage
24 VDC	24 mA	1000±10% Ω	18 VDC	2 VDC

Contact Parameters

Contact Form	2 Form C	Max Contact Rating	50 W
Max Switch Voltage	2.5 kVDC	Max Switch Current	3.0 A
Max Carrying Current	3.2 A	Min Breakdown Voltage	5 kVDC
Max Contact Resistance	300 mΩ	Life Expectancy (Electrical) (at 500 VDC 100mA)	5×10 ⁷ ops

Electrical Specifications

Dielectric Strength (Static,min)	Open contacts	5 kVDC	Insulation Resistance (min./typ.) Rh<45%, 100V Test Voltage	Open contacts	1×10 ¹² Ω
	Contact to coil	5 kVDC		Contact to coil	1×10 ¹² Ω
Operate Time,incl.Bounce		3.0 ms	Capacitance	Across Open Switch	3.3 pF
Reset Time		2.0 ms			

Environmental data

Vibration (10 to 2KHz 1.5mm)	20 G	Shock (1/2 sine wave duration 11ms)	50 G
Operating Temperature	-20℃ ~ 70℃	Storage Temperature	-35℃ ~ 105℃
Soldering Temperature (5 sec. dwell)	260℃	Washability	fully sealed

Example of order marking

Product model	Nominal Coil Voltage	Contact form	Breakdown Voltage	Pin Out	Special code
400-133	Nil	Nil	Nil	Nil	Nil

Remark: RoHS	Make	Li Linmao	TITLE High Voltage Reed Relay P/N 400-133	 Version: 04 Page: 1/1
	Checke	Hu Shu		
	Approved	Dong Hu		
	Date	30th,Dec,2024		