





HVR12-1C01

- High Dielectric Strength Up 1 kVDC Form C
- Low Contact Resistance
- Hermetically Sealed For Long Life
- Excellent Lifetime Characteristics
- Custom Design Available

**Outline Dimension****Unit: mm DIM Tolerance: ±0.3****Layout[Top View]****Marking****Mirelay Reed Relay****HVR12-1C01****Coil Parameters (at 20°C)**

Nominal Coil Voltage	Nominal Current	Coil Resistance	Max Pull-in Voltage	Min Drop-out Voltage
12 VDC	60 mA	200±10% Ω	9 VDC	1 VDC

Contact Parameters

Contact Form	1 Form C	Max Contact Rating	100 W
Max Switch Voltage	240 VDC	Max Switch Current	4.0 A
Max Carrying Current	4.0 A	Min Breakdown Voltage	1 kVDC
Max Contact Resistance	300 mΩ	Life Expectancy (Electrical) (at 50 VDC 10mA)	5×10 ⁷ ops

Electrical Specifications

Dielectric Strength (Static,min)	Open contacts	1 kVDC	Insulation Resistance (min./typ.) Rh<45%, 100V Test Voltage	Open contacts	1×10 ⁹ Ω
	Contact to coil	10 kVDC		Contact to coil	1×10 ¹² Ω
Operate Time,incl.Bounce	3.0 ms	Capacitance	Across Open Switch	2.3 pF	
Reset Time	1.5 ms				

Environmental data

Vibration (10 to 2KHz 1.5mm)	20 G	Shock (1/2 sine wave duration 11ms)	50 G
Operating Temperature	-20°C ~ 70°C	Storage Temperature	-35°C ~ 105°C
Soldering Temperature (5 sec. dwell)	260°C	Washability	fully sealed

Example of order marking

Product model	Nominal Coil Voltage	Contact form	Breakdown Voltage	Pin Out	Special code
HVR	12: 12 VDC	1C: 1 Form C	01: 1 kVDC	Nil	Nil

Remark:

RoHS

Make

Li Linmao

Checke

Hu Shu

Approved

Dong Hu

Date


8th,Jan,2025

TITLE

High Voltage Reed Relay

P/N

HVR12-1C01



Version: 04

Page: 1/1