

HGSR24-1CM

Mercury Wetted Reed Relay

PRODUCT VISUAL

SOURCE IMAGE NOT AVAILABLE

source image

KEY RATINGS

COIL VOLTAGE

24 VDC

OPERATING VOLTAGE

29 VDC

PULL-IN VOLTAGE

18 VDC

DROP-OUT VOLTAGE

2.0 VDC

CONTACT FORM

1 Form C

CONTACT RATING

100 W

OVERVIEW

- ✓ Mercury wetted reed relay with metal or plastic case
- ✓ 100 W contact rating, 500 V switching
- ✓ Long life 2×10^9 operations
- ✓ 1 Form C changeover contact
- ✓ No contact bounce, stable contact resistance

COIL DATA

Coil Voltage	24 VDC
Operating Voltage	29 VDC
Pull-in Voltage	18 VDC
Drop-out Voltage	2.0 VDC
Coil Resistance ($\pm 10\%$)	2650 ohm

CONTACT RATINGS

Contact Form	1 Form C
Contact Rating	100 W
Switch Voltage	500 V
Switch Current	2.0 A
Carry Current	5.0 A
Breakdown Voltage	2000 V
Contact Resistance	30 mohm
Life Expectancy	2000 $\times 10^6$ cycles

ELECTRICAL CHARACTERISTICS

Dielectric Strength Contact/Coil	2000 V
Insulation Resistance Contact/Contact	10^9 ohm
Insulation Resistance Contact/Coil	10^9 ohm
Operate Time	1.25 ms
Reset Time	1.25 ms
Capacitance Open Contacts	4.0 pF
Capacitance Contacts to Coil	10.0 pF

ENVIRONMENTAL / OPTIONS

Storage Temperature	-20 to +105 C
Operate Temperature	-20 to +85 C

MECHANICAL OUTLINE / DIMENSIONS

Outline image recorded in source PDF

CIRCUIT / MARKING / TERMINAL VIEW

Connection figure not available

ORDERING & SOURCE TRACEABILITY

HGSR24-1CM — M metal case / P plastic case options

Source: HGSR12-1CM.pdf

Technical values are preserved from source PDFs / generated metadata. Original outline and circuit figures are reused where available; do not treat artwork proportions as standalone dimensional authority.