

HVSR12-1A08

High Voltage Reed Relay

PRODUCT VISUAL

SOURCE IMAGE NOT AVAILABLE

source image

KEY RATINGS

NOMINAL COIL VOLTAGE

12 VDC

NOMINAL CURRENT

60 mA

MAX PULL-IN VOLTAGE

9 VDC

MIN DROP-OUT VOLTAGE

1 VDC

CONTACT FORM

1 Form A

MAX CONTACT RATING

50 W

OVERVIEW

- High Voltage Reed Relay
- Breakdown up to 8 kVDC
- Custom Design Available
- High Frequency High Power
- Excellent Lifetime Characteristics

COIL DATA

Nominal Coil Voltage	12 VDC
Nominal Current	60 mA
Coil Resistance	200±10% Ω
Max Pull-in Voltage	9 VDC
Min Drop-out Voltage	1 VDC

CONTACT RATINGS

Contact Form	1 Form A
Max Contact Rating	50 W
Max Switch Voltage	6 kVDC
Max Switch Current	3.0 A
Max Carrying Current	5.0 A
Min Breakdown Voltage	8 kVDC
Max Contact Resistance	100 mΩ

ELECTRICAL CHARACTERISTICS

Dielectric Strength, Open Contacts	8 kVDC
Dielectric Strength, Contact to Coil	8 kVDC
Insulation Resistance, Open Contacts	1×10 ¹² Ω
Operate Time incl. Bounce	3.0 ms
Reset Time	1.5 ms
Capacitance, Across Open Switch	1.6 pF

ENVIRONMENTAL / OPTIONS

Vibration	20 G
Shock	50 G
Operating Temperature	-20°C □ 85°C
Storage Temperature	-35°C □ 105°C
Soldering Temperature	260°C
Washability	fully sealed


MECHANICAL OUTLINE / DIMENSIONS

- High Frequency High Power
- Breakdown up to 8 kVDC
- Excellent Lifetime Characteristics
- Custom Design Available



Outline Dimension

Unit: mm DIM Tolerance: ±0.3



CIRCUIT / MARKING / TERMINAL VIEW

Connection figure not available

ORDERING & SOURCE TRACEABILITY

HVSR12-1A08 — High Voltage Reed Relay

Source: HVSR12-1A08.pdf

Technical values are preserved from source PDFs / generated metadata. Original outline and circuit figures are reused where available; do not treat artwork proportions as standalone dimensional authority.