

# MiRelay Product Datasheet

## 12V 2Channel High Current Mercury 5A Wetted Relay HGSR12-2A04

Model: HGSR12-2A04 | Product family: Mercury Wetted Relays | Document code:  
SHR-HGSR12-2A04-12V-2CHANNEL-HIGH-CU | Rev: 2026-05

SHR AUTOSENSOR TECH LIMITED supplies 12V 2Channel High Current Mercury 5A Wetted Relay HGSR12-2A04 under the MiRelay product line for engineering buyers who require reliable switching, sensing, sample purchasing and RFQ support. This English datasheet is newly generated from the verified SHR product index and family-level engineering knowledge; it is not a direct copy of legacy source documents.

### Key selection data

Coil Voltage	12 VDC
Must Operate Voltage	9 VDC
Must Release Voltage	1 VDC
Coil Resistance	600 Ohms
Max Contact Rating	100W
Max Switch Voltage	500VAC Peak/VDC
Max Switch Current	2A
Mounting Type	Through Hole
Termination Style	PC Pin
Package	Bulk
Operating Temperature	-20°C ~ 70°C
Dielectric / Switch Voltage Class	4 kV class
Contact Form	2A contact configuration
Technology	Mercury wetted reed relay for low contact resistance and stable switching
Applications	ATE, instrumentation, pulse switching, low-level measurement
Customization	Coil voltage, lead length, shielding, cable, insulation and mounting options by RFQ
Quality Note	Final electrical ratings must be confirmed against application waveform, load type and environment
Sample / RFQ path	Buy sample online where listed, or request engineering quote at <a href="https://www.reed-relay.com/rfq/">https://www.reed-relay.com/rfq/</a>
Support contact	sales@reed-relay.com   +86 13761571029   www.reed-relay.com

### Recommended RFQ information

- Target part number or competitor cross-reference
- Switching voltage/current, carry current, load type and waveform
- Coil voltage, contact form, package or lead configuration
- Required quantity, sample needs, delivery target and certification constraints
- Application environment: temperature, insulation, leakage, vibration and safety requirements

### Important engineering note

Ratings and dimensions can vary by exact option code and customer configuration. Use this document for initial selection only. SHR AUTOSENSOR TECH LIMITED will confirm final drawings, datasheets, lead time and pricing during RFQ review.